

VOLVO CONSTRUCTION EQUIPMENT MATRIS REPORT

Machine model EC300D	SerialNo 210273	Operating Hours 4357.4	Reading Date 11/04/2019
Company name Volvo Remarketing	Dealer	Report Issuer	
Contact name	Technician lvcetech	Primary Application Civil engineering/Heavy construction	
Site	Workorder	Ground Condition	

MATRIS Reading, Summary / Recommendation




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Main equipment	Type	Equipment
	Track chain	
	X3 piping	
	Main Attachment	
	Attachment Interface	
	Hydraulic Fluid	
	X1 Piping	
	Hose Rupture Valve on Boom	
	Hose Rupture Valve on Arm	
	X1 return filter	



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

This diagram shows the fuel consumption distribution rate on each work mode.

Distribution of each work mode is shown on top of its column in rate

Explanation:

Y-axis: The rate of the fuel consumption on each work mode.

X-axis: The work mode (10 steps in total)




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Distribution of each work mode is shown on top of its column in rate

Average fuel consumption per hour is listed below the diagram



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:


The graph shows the distribution of the operating time for the machine. The operating time is defined as the time with engine on

Blue sector = Engine is running, but attachments and tracks are not moved or operated .

Green sector = Machine in work with the move of attachments and tracks



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019





Definition:

The diagram describes the amount of fuel consumed per engine speed mode distribution.



Total amount of fuel consumed (m3) in above means that the sum of the fuel while it consumed for engine ON. The values above distribution were calculated from theoretical calculation with logged data in V-ECU so it can be some different from actual performance in field.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019





Definition:

The diagram describes Hydraulic Cooling fan speed control, Current (mA) distribution, on fan speed Control..

Total time (hours) in above means the sum of the time for Hydraulic Cooling fan operation.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019


Cooling fan, Normal-Reverse rotation distribution (%)

■ Normal rotation
 ■ Reverse rotation



Total operating time (h) = 4358.0


Reverisble fan, Time setting distribution (h) at Auto 1 mode




Total operating time at Auto 1 mode (h) = 0.0



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes Engine boost air temperature distribution of the machine when the engine is on.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

This diagram shows the distribution of the engine work mode in percentage of time when ECO mode is engaged.

Explanation:

Y-axis: The percentage of the operating hours on each work mode when ECO mode is engaged.

X-axis: The engine work mode (10 step in total)

Distribution of each work mode is shown on top of the column in percentage.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

The sum of time distribution in percentage is 100%

Total time (h) is listed below the diagram.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

This diagram shows the distribution of the engine work mode in time percent.

Distribution of each work mode is shown on top of the column in percentage.

Explanation:

Y-axis: The percentage of the operating hours on each work mode.

X-axis: The engine work mode (10 step in total)



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019


Distribution of each work mode is shown on top of the column in percentage.

The sum of time distribution in percentage is 100

Total time (h) is listed below the diagram



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph describes the engine speed distribution, in hours.

The sum of all bars = total time of engine running.

Explanation:

Y-axis: Engine running time in hours.

X-axis: Engine speed in rpm.

Green bars = Normal engine speed range.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Red bars =The engine speed has exceeded the maximum design speed.

Exceeding the maximum design speed may cause severe damage to the engine.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph describes the engine speed distribution in percent of time.

The sum of all bars=100% of engine running time.

Explanation:

Y-axis: Engine running time in percent.

X-axis: Engine speed in rpm.

Green bars = Normal engine speed range

Blue bar = Idling interval.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Red bars =The engine speed has exceeded the maximum design speed.


Exceeding the maximum design speed may cause severe damage to the engine



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



This graph shows the distribution of the engine load.

Blue bar: Low load

Green bar: Normal load


Yellow bar: Excessive load

Load distribution for each bar is shown on top of its column in percentage.

The sum of bars is 100%.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph describes the average number of engine starts per engine running hour.

Explanation:

X-axis: Number of average starts per hour.

The actual time used for calculation, is time with engine on

If the fuel consumption is high one reason may be that the engine is not turned off often enough, perhaps machine is left idling for long periods. Check " Machine utilization".

The value can vary a lot depending on in which application the machine is used.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

To see at which different temperatures engine is started see" Start at different engine temperatures."

Green bar = Number of average starts per hour



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:


This graph shows the distribution of delayed time at low idle speed until the engine is turned off.

The delayed time distribution for each bar is shown on top of its column in percentage.

The sum of bars is 100%.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The diagram shows the number of stops at high idle (I1 ~ P mode).

Green bars = Normal engine stop

Red bars = Abnormal engine stop

Engine stops at a high idle can cause server damage to the turbo charger due to shortage of the oil lubrication. The engine should be stopped at low idle(I2 mode).

Explanation:

Y-axle: Number of engine stop at each work mode.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019


X-axle: Work mode.

Distribution of each work mode is shown on top of its column in number.

Total number of shut down is listed below the diagram.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph shows the distribution of engine coolant temperature, at the starting moment.

Explanation:

Y-axis: Number of engine starts

X-axis: Engine coolant temperature.

A great proportion of engine wear is due to cold starts. Try to avoid extremely cold starts. Try using an electric coolant heater.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Under the graph the total number of engine starts is displayed.

Also see " *Number of starts / hour*" to get a complete picture of engine starting.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Low coolant level
Total number of occurrences = 1260

	Op hours	Year	Month	Day	Hour	Minute	Duration (sec)
*	4330	2018	2	8	4	49	255
*	4330	2018	2	8	4	34	98
*	4331	2018	2	8	5	35	83
*	4332	2018	2	8	20	33	359
*	4332	2018	2	8	20	41	6
*	4332	2018	2	8	20	46	91
*	4333	2018	2	8	22	12	169
*	4335	2018	2	8	23	39	87
*	4336	2018	2	9	0	22	63
*	4337	2018	2	9	1	40	1531
*	4338	2018	2	9	3	10	1067
*	4338	2018	2	9	2	31	1555
*	4339	2018	2	9	3	32	962
*	4339	2018	2	9	3	52	41
*	4339	2018	2	9	3	55	6
*	4340	2018	2	9	4	27	125
*	4340	2018	2	9	20	23	1860
*	4340	2018	2	9	20	56	6
*	4340	2018	2	9	20	59	48
*	4340	2018	2	14	4	57	42

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Criteria :

In order for an occurrence of low engine coolant level to be recorded in a data point, the count to increment by 1 the engine coolant level state must change from "normal" to "low."



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Low engine oil level at start
Total number of occurrences = 1

	Op hours	Year	Month	Day	Hour	Minute
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	0	2000	0	0	0	0
*	4145	2018	1	3	1	42

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Criteria :

In order for an occurrence of low engine oil level to be recorded in a data point and the count to increment by 1, an Alarm shall have been received at start up of machine



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Low Engine Oil Pressure
Total number of occurrences = 0

	Op hours	Year	Month	Day	Hour	Minute	Duration (sec)
A	0	2000	0	0	0	0	0
R	0	2000	0	0	0	0	0
Q	0	2000	0	0	0	0	0
P	0	2000	0	0	0	0	0
O	0	2000	0	0	0	0	0
N	0	2000	0	0	0	0	0
M	0	2000	0	0	0	0	0
L	0	2000	0	0	0	0	0
K	0	2000	0	0	0	0	0
J	0	2000	0	0	0	0	0
I	0	2000	0	0	0	0	0
H	0	2000	0	0	0	0	0
G	0	2000	0	0	0	0	0
F	0	2000	0	0	0	0	0
E	0	2000	0	0	0	0	0
D	0	2000	0	0	0	0	0
C	0	2000	0	0	0	0	0
B	0	2000	0	0	0	0	0
S	0	2000	0	0	0	0	0
T	0	2000	0	0	0	0	0

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating hours is displayed in the first column, followed by year, month, day, hour



**Extreme
(bar)**

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :

The extreme value column displays the most extreme value during the event.

Criteria :

In order for an occurrence of low engine oil pressure to be recorded in a data point and the count to increment by 1, the engine oil pressure state must change from "normal" or "error" to "low." The event of low transmission oil pressure will end when the status changes from "low" back to "normal" or "error."





Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Fuel Filter Clogging
Total number of occurrences = 10

Op hours	Year	Month	Day	Hour	Minute	Duration (min)
3873	2017	11	8	2	30	44
3031	2017	2	23	0	15	1
3028	2017	2	22	20	51	200
2281	2016	9	10	8	49	4
2281	2016	9	10	10	6	374
2222	2016	8	25	9	55	336
1281	2015	10	4	13	28	23
1281	2015	10	4	14	45	1
786	2015	9	24	9	33	7
786	2015	9	24	10	13	1
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Low Air filter pressure
Total number of occurrences = 0

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month, day, hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed.

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Criteria :

The criteria to get an registration, is that the alarm signal for air filter clogged is active, and that the diesel engine is running.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

**High Charge air temperature
Total number of occurrences = 2**

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)	Extreme (° C)
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
1306	2015	10	9	15	25	2111	77
1334	2015	10	24	13	21	6795	78

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :

The extreme value column displays the most extreme value during the event.

Criteria :

In order for an occurrence of high engine charge air temperature to be recorded and the count to increment by 1, the engine charge air temperature must change from “normal” to “high.” The event of high engine charge air temperature will end when the status changes from “high” back to “normal.”



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Regeneration ignored
Total number of ignored regenerations 62

	Op hours	Year	Month	Day	Hour	Minute	Duration (min)
*	2642	2016	11	30	15	55	34
*	3047	2017	3	7	3	53	1
*	3047	2017	3	7	21	12	55
*	3047	2017	3	7	3	54	11
*	3047	2017	3	7	3	28	9
*	3047	2017	3	7	3	27	1
*	3047	2017	3	7	3	38	15
*	3047	2017	3	7	2	56	2
*	3047	2017	3	7	2	54	2
*	3047	2017	3	7	3	20	7
*	3049	2017	3	7	22	41	36
*	3369	2017	5	12	0	57	84
*	4304	2018	2	3	0	58	84
*	4347	2018	3	18	4	35	8
*	4348	2018	3	28	21	39	47
*	4348	2018	3	28	20	25	29
*	4348	2018	3	18	4	48	0
*	4353	2018	7	4	23	16	2
*	4353	2018	7	5	2	31	105
*	4353	2018	7	4	4	55	6



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Regeneration aborted
Total number of occurrences = 63

Op hours	Year	Month	Day	Hour	Minute	Reason
2769	2016	12	29	23	25	1
3656	2017	8	23	22	39	1
3710	2017	9	7	21	13	1
3710	2017	9	8	3	17	1
3722	2017	9	12	20	9	1
3723	2017	9	12	21	24	1
3723	2017	9	12	22	21	1
3801	2017	10	25	1	6	1
3931	2017	11	21	23	52	1
3931	2017	11	22	5	25	1
4112	2017	12	27	6	22	1
4170	2018	1	6	0	55	2
4252	2018	1	26	5	18	1
4302	2018	2	2	6	28	1
4339	2018	2	9	3	28	1
4339	2018	2	9	3	48	1
4346	2018	3	11	5	3	1
4351	2018	5	19	3	37	1
4352	2018	6	27	0	54	1
4353	2018	6	28	4	33	1



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Regeneration duration
Total number of occurrences = 501

Op hours	Year	Month	Day	Hour	Minute	Duration (min)
4241	2018	1	24	4	30	33
4251	2018	1	26	4	58	20
4252	2018	1	26	20	4	33
4262	2018	1	27	5	30	33
4270	2018	1	28	3	21	32
4280	2018	1	31	4	53	34
4291	2018	2	1	5	25	33
4302	2018	2	2	6	18	10
4305	2018	2	3	1	45	37
4317	2018	2	7	1	39	34
4326	2018	2	7	23	43	34
4337	2018	2	9	1	28	2
4339	2018	2	9	3	31	2
4339	2018	2	9	3	52	35
4346	2018	3	11	5	0	3
4348	2018	3	28	21	52	34
4351	2018	5	19	3	31	6
4352	2018	6	27	0	45	9
4352	2018	6	28	4	26	7
4354	2018	7	5	3	43	33



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

**High engine coolant temperature
Total number of occurrences = 75**

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)	Extreme (° C)
2951	2017	2	2	22	35	118	106
2953	2017	2	3	0	3	1719	111
2957	2017	2	3	4	23	975	108
2959	2017	2	3	19	42	125	108
2959	2017	2	3	19	40	7	103
2963	2017	2	3	23	47	6	105
2963	2017	2	4	2	9	71	108
2963	2017	2	4	2	8	46	117
2964	2017	2	4	2	53	1193	106
2965	2017	2	4	3	43	5	105
2965	2017	2	4	3	45	264	112
3027	2017	2	22	4	40	37	103
3464	2017	6	1	23	37	99	106
3465	2017	6	2	1	21	120	106
3465	2017	6	2	1	49	11	107
3735	2017	9	20	2	17	233	107
3735	2017	9	20	2	27	9	105
3735	2017	9	20	2	34	232	102
3748	2017	9	28	2	7	104	103
3898	2017	11	15	2	33	1	100

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month, day, hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed.

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :

The extreme value column displays the most extreme value during the event.

Criteria :

The criteria to get an registration, is that the alarm signal for high engine coolant temperature is active and that the diesel engine is running.





Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Water level warning in water separator
Total number of occurrences = 0


Op hours	Year	Month	Day	Hour	Minute	Duration (min)
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0
0	2000	0	0	0	0	0



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes auto-manual mode selection distribution of HVAC system in machine while it Works. The share of each mode compared to Total time of HVAC operation is displayed.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

HVAC air temperature setting in auto control mode distribution (h)




Definition:

The diagram describes air temperature setting distribution for HVAC auto control mode established by operator in Cabin



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes ambient temperature distribution of the machine while machine operates.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph shows the total time of AC compressor engagement.

Explanation:

Green bar: Total time in hours, AC compressor has been engaged.

Under the graph the total engine running time (in hours) is displayed.

Total number of AC compressor activations is also displayed.




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

-



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes air flow direction distribution for HVAC manual control mode established by operator in Cabin.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The diagram describes air blower motor speed distribution for HVAC manual control mode established by operator in Cabin.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

AC High Pressure
Total number of occurrences = 0

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)	Extreme (° C)
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :

The extreme value column displays the most extreme value during the event.

Criteria :

Logging is performed when, High AC Pressure signal is active. Ambient temp is viewed.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

**AC Boiling Protection
Number of engagements = 0**

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)	Extreme (° C)
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :

The extreme value column displays the most extreme value during the event.

Criteria :

Logging is performed when, Boiling protection signal is active. Ambient temp is viewed.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

AC System Cut Out Pressure
Total number of occurrences = 8

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)	Extreme (° C)
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
0	2000	0	0	0	0	0	0
1	2012	2	18	6	51	4	-5
2	2012	2	18	8	52	4	-3
2	2012	2	18	8	23	0	0
2	2012	2	18	7	42	1	-3
8	2013	1	6	10	21	4	-14
9	2013	1	8	0	50	4	-7
324	2014	11	18	14	15	472	-6
3462	2017	6	1	20	55	1417	-14

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :


The extreme value column displays the most extreme value during the event.

Criteria :

Logging is performed when, AC cut out pressure signal is active. Ambient temp is viewed.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph shows the time distribution of the temperature, while engine running.

Explanation:

Y-axis: Time

X-axis: Temperature distribution in classes.

Blue bar = Warm-up phase.

During the engine warm-up phase, this temperature region is passed.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

It is normal to have registrations in this region.

Green bar = Normal working temperature. The Major part of the registrations shall be in this region.


Yellow bar = High working temperature. It is normal to have some registrations in this region.

Red bar = Alarm.

Registrations in this region is not normal, running in this region may cause severe damage.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph shows the time distribution of the temperature, while engine running.

Explanation:

Y-axis: Time

X-axis: Temperature distribution in classes.

Blue bar = Warm-up phase.

During the engine warm-up phase, this temperature region is passed.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

It is normal to have registrations in this region.

Green bar = Normal working temperature. The Major part of the registrations shall be in this region.


Yellow bar = High working temperature. It is normal to have some registrations in this region.

Red bar = Alarm.

Registrations in this region is not normal, running in this region may cause severe damage.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The graph describes the operating hours (%) for hydraulic hammer/shears on each engine control mode .

Recommended to use green column mode of the hammer operation.

I2 = Idle 2

I1 = Idle 1

F3= Fine control 3

F2= Fine control 2



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

F1= Fine control 1

G3 = General 3

G2 = General 2


G1 = General 1

H = Heavy Duty

P = Power max



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The diagram describes Power boosted operating time distribution, when main relief pressure increases on working operation modes. In this diagram, the sum of time (%) of each working operation mode can exceed 100%. It means that customer has been operated several working operations at the same time.


Total operating time with power boosted (hours) in above means sum of the time for Hydraulic Power boosted operation. The base for the percentage calculation is Total operating time with power boost. Time(%) on each working operation mode except travel and F mode above is the time, after the operator press power boost button on the joystick and until main relief pressure is recovered to default pressure.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

This graph shows operating hour distributions on each travel speed for total travel time.

Blue sector: Travel switch in low position

Green sector: Travel switch in high position

Explanation:

Distribution of each travel time is shown on right of its sector in percentage

The sum of travel time in percentage is 100




Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

Total travel time is listed below the diagram



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes Pump outlet pressure of 2 Pumps for travel and swing operation distribution. In case operator use several operations at the same time, this pressure distribution for travel and swing operation can be different from actual operating pressure distribution for travel and swing operation in field.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes Pump outlet pressure of 2 Pumps distribution.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes hydraulic working operation mode distribution.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The diagram describes the distribution of hydraulic pilot pressure in specified operation



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

**High hydraulic oil temperature
Total number of occurrences = 36**

Op hours	Year	Month	Day	Hour	Minute	Duration (sec)	Extreme (° C)
3863	2017	11	4	2	26	254	108
3863	2017	11	4	2	22	54	106
3863	2017	11	4	2	21	4	105
3863	2017	11	4	2	24	13	105
3864	2017	11	4	3	9	24	105
3865	2017	11	4	4	38	1442	120
3865	2017	11	4	4	28	562	110
3865	2017	11	4	4	17	558	114
3869	2017	11	7	22	4	22	105
3869	2017	11	7	22	6	910	116
3869	2017	11	7	22	0	102	108
3873	2017	11	8	1	59	18	105
3873	2017	11	8	2	0	83	107
3875	2017	11	8	20	59	182	109
3876	2017	11	8	21	25	17	105
3876	2017	11	8	21	29	42	107
3876	2017	11	8	21	34	85	107
3876	2017	11	8	22	21	2021	119
3878	2017	11	9	0	42	1136	115
4244	2018	1	25	21	18	14	105

Definition :

This type of table shows the latest occasions when a specific event has occurred. When a specified criteria is fulfilled a registration is made. Each table row corresponds to one occasion. Operating



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019

hours is displayed in the first column, followed by year, month , day , hour and minute to show when an event has occurred.

The rows are not ordered chronological (The latest event may be in the middle).

Only one event per minute is registered.

Over the table the total number of events is displayed

Duration :

The duration of each event is shown after the timestamp of the event.

The duration is counted as long as the criteria is fulfilled.

Extreme value :


The extreme value column displays the most extreme value during the event.

Criteria :

Logging is performed when, Alarm high hydraulic oil temperature , is active.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019




Definition:

The diagram describes the distribution of Rotator operating hours on mode.



Machine model	SerialNo	Operating Hours	Reading Date
EC300D	210273	4357.4	11/04/2019



Definition:

The diagram describes X1 hydraulic oil flow control distribution of the machine while machine operates.

